

ComColor™ 7150 / 7110



Specifications

		ComColor 7150	ComColor 7110
Print Type		Line-type inkjet system	
Ink Type		Oil-based pigment ink (Cyan/Magenta/Yellow/Black)	
Resolution		Standard: 300 dpi (main scanning direction) × 300 dpi (subscanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (subscanning direction)	
Number of Gray Levels		For each CMYK color (8 gray levels)	
Data Processing Resolution		Standard: 300 dpi × 300 dpi Fine: 300 dpi × 600 dpi Line smoothing: 600 dpi × 600 dpi	
Warm-up Time		2 min. 45 sec. or less (at room temperature of 20°C (68°F))	
First Print Time		5 sec. or less ^{*1} (when copying A4/Letter long-edge feed using color mode)	
Continuous Print Speed ^{*2*3}	A4 long-edge feed	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)	
	Letter long-edge feed	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)	
	A4 short-edge feed	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)	
	Letter short-edge feed	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)	
	B4/Legal short-edge feed	Simplex: 76 ppm, Duplex: 38 sheets/minute (76 ppm)	
	A3 short-edge feed	Simplex: 66 ppm, Duplex: 33 sheets/minute (66 ppm)	
	Ledger short-edge feed	Simplex: 66 ppm, Duplex: 33 sheets/minute (66 ppm)	
Paper Size	Standard Tray	Maximum: 340 mm × 550 mm (13 3/8" × 21 5/8") Minimum: 90 mm × 148 mm (3 9/16" × 5 13/16")	

	Feed Tray	Maximum: 297 mm × 420 mm (11 11/16" × 17") Minimum: 182 mm × 182 mm (7 3/16" × 7 3/16")	-
Printable Area		Maximum: 314 mm × 548 mm (12 3/8" × 21 9/16")	
Guaranteed Print Area *4		Standard: Margin width of 3 mm (1/8") Maximum: Margin width of 1 mm (0.04")	
Paper Weight	Standard Tray	46 gsm to 210 gsm (12-lb bond to 56-lb bond) (plain paper)	
	Feed Tray	52 gsm to 104 gsm (14-lb bond to 28-lb bond) (plain paper)	-
Paper Feed Method/ Paper Tray Capacity	Standard Tray	Height up to 110 mm (4 5/16")	
	Feed Tray	Height up to 50 mm (1 15/16") (× 3 trays)	-
Output Tray Capacity	Standard	Height up to 60 mm (2 3/8")	
Page Description Language		RISORINC/C	
Supported Protocols		TCP/IP, HTTP, HTTPS (SSL), DHCP, ftp, lpr, IPP, SNMP, Port 9100 (RAW port), IPv4, IPv6, IPsec	
Supported Operating Systems		Microsoft® Windows® XP (32-bit), Microsoft® Windows Server® 2003 (32-bit/64-bit), Microsoft® Windows Server® 2003 R2 (32-bit/64-bit), Microsoft® Windows Vista® (32-bit/64-bit), Microsoft® Windows Server® 2008 (32-bit/64-bit), Microsoft® Windows Server® 2008 R2 (64-bit), Microsoft® Windows® 7 (32-bit/64-bit), Microsoft® Windows® 8 (32-bit/64-bit), Microsoft® Windows Server® 2012 (64-bit)	
Network Interface		Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T	
Memory Capacity		1 GB	
Hard Disk *5	Capacity	320 GB	
	Available Space	280 GB	
Operating System		Linux	
Power Source		AC 100-240 V, 10-5 A, 50-60 Hz	
Power Consumption		Maximum: 1,000 W Ready *6: 150 W or less Sleep *7: 5 W or less Stand-by: 0.5 W or less	
Operating Noise		Max. 66 dB *8	

Operating Environment	Temperature: 15°C to 30°C (59°F to 86°F) Humidity: 40% to 70% RH (non-condensing)	
Dimensions (W × D × H)	In use: 1,220 mm × 705 mm × 1,030 mm (48 1/32" × 27 3/4" × 40 9/16") Cover and feed trays closed: 1,155 mm × 705 mm × 1,010 mm (45 15/32" × 27 3/4" × 39 3/4")	
Required Space (W × D × H)	Cover and feed trays opened: 1,220 mm × 1,240 mm × 1,030 mm (48 1/32" × 48 13/16" × 40 9/16")	
Weight	Approx. 171 kg (376 lb)	Approx. 149 kg (328 lb)

- *1: Within 10 minutes after the last print job.
- *2: When using plain paper and recycled paper (85 gsm (23-lb bond)), and density setting 3 (Standard). Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].
- *3: The continuous print speed varies depending on the type of optional output equipment connected. Multifunction Finisher: Max. 120 sheets/minute (A4 long-edge feed simplex). Face Down Offset Stapler: ComColor 7150/7110: Max. 120 sheets/minute (A4 long-edge feed simplex).
- *4: The margin when printing envelopes is 10 mm (3/8"). The guaranteed area when printing images is the area enclosed within 3 mm (1/8") of the edges of the paper.
- *5: One gigabyte (GB) is calculated as one billion bytes.
- *6: Without printing and temperature adjustment operation.
- *7: When setting [Power consumption (in sleep)] to [Low].
- *8: When printing without optional equipment connected.
- RISO logo and ComColor are either registered trademarks or trademarks of Riso Kagaku Corporation. Microsoft, Windows, Windows Server, and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.
- Specifications are subject to change without notice. Details may vary depending on the region.

Function

Secure print, Admin. settings

- · Compatible with authentication server setting, IPv6 and IPSec
- · Specifiable a job name and owner name
- · PIN code protection when you select [PDF] as the saving format of scanned data

Print quality control

- · Bar-code area definition
- · Line smoothing
- · Envelope image enhancement

Print functions

- · Direct printing from a USB flash drive
- · Data compression
- · Custom paper entry
- · Program print **7150**
- · Auto-rotate
- · Blank page removal
- · Direct access entry
- · Stamp page/date

- · Watermark
- · Base color level
- · Draft Print
- · Staple speed priority
- · Interrupt copy
- · Original size checking
- · Mixed size original **7150**
- · Sorting, Multi-up printing(single and plural)
- · Slip sheet **7150**
- · Select layout