

Specifications for imageRUNNER ADVANCE C5500i Series

Type	Colour Laser Multifunctional	
Maximum Original Size	A3	
Supported Media Sizes	Cassette 1:	A4, B5, A5, A5R
		Custom Size: 98.0 x 148mm to 297 x 215.9mm
	Cassette 2:	A3, B4, A4, A4R, B5, B5R, A5R, Foolscap, India Legal, F4A
		Custom Size: 98.0 x 182mm to 304.8 x 457.2mm
Multi Purpose Tray:	A3, B4, A4, A4R, B5, B5R, A5R 139.7 x 182mm to 297 x 431.8mm	
Supported Media Weights	Cassette	52 to 256gsm
	Multi Purpose Tray	52 to 300gsm
Paper Capacity (80gsm)	Cassette 1, 2:	550 sheets
	Multi Purpose Tray:	100 sheets
Warm-Up Time	30 seconds or less	
Memory	Standard: 4GB RAM	
Hard Disk Drive	Standard:	250GB
	Maximum:	1TB
Interface	Network	Standard: 1000Base-T / 100Base-TX / 10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
	Others	Standard: USB 2.0 x 2 (Host), USB 3.0 x 1 (Host), USB 2.0 x 1 (Device)
Power Supply	220 - 240V ($\pm 10\%$) , 50 / 60Hz (± 2 Hz) , 6Amp	

Power Consumption	Maximum	Approx. 1.8kW
	Standby	Approx. 67.9W
Toner Yield (A4, 5% coverage)	Black: 69,000 Yellow / Magenta / Cyan: 60,000 (Regular), 26,000 (Low)	
Dimensions (W x D x H)	620 x 742 x 950mm	
Installation Space (W x D)	943 x 1,176mm (when Multi-purpose tray Extended + Cassette Drawers open)	
Weight	Approx. 143kg (Including the toner bottle)	
Copy Specification		
Copy Speed	iR-ADV C5560i:	60ppm (A4) 32ppm (A3)
	iR-ADV C5550i:	50ppm (A4) 27ppm (A3)
	iR-ADV C5540i:	40ppm (A4) 22ppm (A3)
	iR-ADV C5535i:	35ppm (A4) 18ppm (A3)
First Copy Output Time	iR-ADV C5560i:	Approx. 2.9 seconds or less (BW), Approx. 4.5 seconds or less (CL)
	iR-ADV C5550i:	Approx. 3.5 seconds or less (BW), Approx. 5.2 seconds or less (CL)
	iR-ADV C5540i:	Approx. 4.1 seconds or less (BW), Approx. 6.1 seconds or less (CL)
	iR-ADV C5535i:	Approx. 4.9 seconds or less (BW), Approx. 7.4 seconds or less (CL)
Magnification	25% – 400% (1% Increments)	

Multiple Copies / Prints	Up to 999 copies	
Print Specification		
PDL	Standard: UFR II, PCL6 Optional: Adobe PS 3	
Print Resolution	1,200 x 1,200dpi, 600 x 600dpi	
Supported OS	UFR II	Server 2003 / Server 2003 R2 Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Server 2012 / Windows 8.1 / Server 2012 R2 / Windows 10, MAC OS X (10.5.8 or later)
	PCL:	Server 2003 / Server 2003 R2 Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Server 2012 / Windows 8.1 / Server 2012 R2 / Windows 10
	Adobe PostScript 3:	Server 2003 / Server 2003 R2 Vista / Server 2008 / Windows7 / Server 2008 R2 / Windows 8 / Server 2012 / Windows 8.1 / Server 2012 R2 / Windows 10, MAC OS X (10.5.8 or later)
Mac-PPD	MAC OS 9.1 or later, MAC OS X (10.3.9 or later),	
Network Protocol	IP / Mac Address Filtering, IPsec, SSL / TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv4 / IPv6, SMTP Authentication, POP Authentication before SMTP	
Scan and Send Specification		
Type	Single-pass Duplexing Automatic Document Feeder	
Document Feeder Paper	150sheets (80gsm)	

Capacity		
Scan Resolution	100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Scan Speed	Single-sided (BW):	80ipm (300pi) / 80 ipm (600dpi)
	Single-sided (Colour):	80ipm (300dpi) / 60 ipm (600dpi)
	Double-sided (BW):	160ipm (300dpi) / 150ipm (600dpi)
	Double-sided (Colour):	160ipm (300dpi) / 80ipm (600dpi)
Destinations	E-mail / Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)	
Address Book	LDAP (2,000) / Local (1,600) / Speed dial (200)	
File Format	Standard:	JPEG, TIFF , PDF / XPS (Compact), PDF (PDF / A-1b, Optimize for Web, Apply Policy)
	Optional:	Outline PDF (Trace & Smooth, Encrypted), PDF / XPS (Digital Signature), PDF / XPS (Searchable), Office Open XML (PowerPoint, Word)