

Specifications for DR 6030C

Type	Desktop sheet-fed scanner	
Document Feeding	Automatic or manual sheet feeding	
Document Size		
Width	53 – 300mm (2 – 11.8in.)	
Length	70 – 432mm (2.75 – 17.01in.)	
	Long Document Mode:	up to 3,000mm (118.1in.)
Document Thickness and Weight		
U-Turn path	Automatic feeding:	0.06 – 0.15mm, 52 – 128g/m ² (14 – 32lb. bond)
	Manual Feeding:	0.05 – 0.2mm, 42 – 157g/m ² (11 – 40lb. bond)
Straight path	Automatic feeding:	0.06 – 0.15mm, 52 – 128g/m ² (14 – 32lb. bond)
	Manual Feeding:	0.05 – 0.66mm, 42 – 546g/m ² (11 – 144lb. bond)
Business Card Size and Thickness		
Size	53.9 x 85.5mm (2.12 x 3.37in.)	
Thickness	0.76 ± 0.08mm (0.03 ± 0.003in.)	
Feeding Capacity	10mm stack or 100 sheets of 80g/m ² (20lb. bond)	
Scanning Element	3-line CMOS CIS	
Light Source	LED (red, green, and blue)	
Scanning Side	Simplex / Duplex	

Scanning Modes	Black and White, Error Diffusion, High-Speed Text Enhancement, Advanced Text Enhancement, Advanced Text Enhancement II, 256-level Grayscale, 24-bit Colour, Auto Color Detection	
Scanning Resolutions	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Scanning Speed (A4 / LTR, Portrait)		
Black and White	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 120ipm (Duplex)
256-level Grayscale	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 120ipm (Duplex)
24-bit Colour	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 84ipm (Duplex)
Interfaces	SCSI-III / Hi-Speed USB 2.0	
Scanner Driver	ISIS / TWAIN	
Useful Functions	Ultrasonic Double Feed Detection, Continuous Mode, Moire Reduction, Prevent Bleed Through / Remove Background, Punch Hole Removal, Color Dropout, Auto Page Size Detection, Text Orientation Recognition, Skip Blank Page, Deskew, MultiStream™, Prescan, User Preferences, Skew Detection, Gamma Correction, Remove Border, Isolated Point Removal, Edge emphasis, Add-on	
Power Requirements	AC220 - 240V (50 / 60Hz)	

Power Consumption	46.5W (Scanning), 3.7W (Sleep Mode)	
Operating Environment	10 – 32.5°C (50 – 90.5°F)	
	Humidity:	20 – 80% RH
Dimensions (W x D x H)	Feed trays closed:	398.4 x 312 x 191.4mm (15.6 x 12.3 x 7.5in.)
Weight	Approx. 10.5kg (23lb.)	
Options / Consumables	Barcode Module, Exchange Roller Kit	

Specifications are subject to change without notice.

- When scanning documents using ADF.
- Actual scanning speed may vary depending on your system configuration and PC.