

Specifications for DR X10C

Type	Desktop sheetfed scanner	
Document Feeding	Automatic or manual sheet feeding	
Document size	Width:	50.8 – 305mm (2 – 12.01in.)
	Length:	70 – 432mm (2.76 – 17.01in.)
Document thickness and weight	Automatic feeding:	0.06 – 0.15mm, 52 – 128g/m ² (14 – 32lb. bond)
	Manual feeding:	0.05 – 0.30mm, 42 – 255g/m ² (11 – 64lb. bond)
Feeding capacity	Up to 500 sheets of good quality paper (48mm or less including page curl)	
Scanning element	3-line CMOS CIS	
Light Source	LED (red, green, and blue)	
Scanning Side	Simplex / Duplex	
Scanning Modes	Black and White, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II 256-level Grayscale 24-bit Colour	
Scanning Resolutions	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Scanning speed* ¹ (A4 / LTR, Portrait, 200dpi)		
Portrait	Black and White:	100ppm (Simplex) / 200ipm (Duplex)
	Grayscale:	100ppm (Simplex) / 200ipm (Duplex)
	Colour:	100ppm (Simplex) / 200ipm (Duplex)

Landscape	Black and White:	130ppm (Simplex) / 260ipm (Duplex)
	Grayscale:	130ppm (Simplex) / 260ipm (Duplex)
	Colour:	130ppm (Simplex) / 260ipm (Duplex)
Useful functions	Job Function, Ultrasonic Double Feed Detection, Staple Detection, Selectable Background Colour, Dust Countermeasures, Auto USB Power Switching, Auto Colour Detection, Moiré Reduction, Prevent Bleed Through / Remove Background, User Registration, Skip Blank Page, Auto Page Size Detection, Deskew, Batch Separation, Text Orientation Recognition, Black Border Removal, Punch Hole Removal, Folio, Long Document Mode, Colour Dropout / Enhancement (R/G/B/Custom), MultiStream™	
Interfaces	Dual Interface (SCSI-3 & High-Speed USB2.0)	
Software	ISIS / TWAIN Driver, Job Registration Tool, CapturePerfect 3.0	
Power requirements	AC 100V (50 / 60Hz), AC 120V (60Hz), AC 220 – 240V (50 / 60Hz)	
Power Consumption	Scanning:	125W
	Sleep mode:	4.2W (AC 220 – 240V: 4.5W)
	Power Turned Off:	0W
Operating environment	10 – 32.5°C (50 – 90.5°F)	
	Humidity:	20 – 80% RH
Dimensions (W x D x H)	528 x 563 x 375mm (20.79 x 22.17 x 14.77in.), with trays closed	
Weight	Approx. 39kg (86lb.)	
Optionals	Pre-Imprinter Unit, Post-Imprinter Unit, Patch Code	

	Decoder, Barcode Module III
Consumables	Exchange Roller Kit (Feed roller, Retard roller, Pick roller), Cleaning Sheets (30), Ink Cartridges for Imprinter

Specifications are subject to change without notice.	
•	Actual scanning speed may vary depending on your system configuration and PC.
*1	When scanning documents using ADF.
	Maximum hardware speed.