

## Specifications for DR-G1100 / 1130

Type	Desktop sheet-fed scanner	
Document Feeding	Automatic or manual sheet feeding	
Document size		
Width	50.8 – 305mm	
Length	70 – 432mm	
	Long Document Mode:	up to 3,000mm
Document thickness and weight		
Continuous Feeding	20 – 209g/m <sup>2</sup> , 0.04 – 0.25mm	
Non-Separation Mode	20 – 255 g/m <sup>2</sup> , 0.04 – 0.3mm	
Feeding Capacity	48mm stack or 500 sheets of 80 g/m <sup>2</sup>	
Scanning Element	3-line CMOS CIS	
Light Source	LED (red, green, and blue)	
Scanning Side	Simplex / Duplex	
Scanning Modes	Black and White, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II, 256-level Grayscale, 24-bit Color, Auto Colour Detection	
Scanning Resolutions	150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Scanning speed* <sup>1</sup> (A4 / LTR, 200dpi)		
B&W	Portrait:	DR-G1130: 100ppm (Simplex) / 200ipm (Duplex)
		DR-G1100: 75ppm (Simplex) /

		150ipm (Duplex) Landscape
	Landscape:	DR-G1130: 130ppm (Simplex) / 260ipm (Duplex)
		DR-G1100: 100ppm (Simplex) / 200ipm (Duplex)
Grayscale	Portrait:	DR-G1130: 100ppm (Simplex) / 200ipm (Duplex)
		DR-G1100: 75ppm (Simplex) / 150ipm (Duplex)
	Landscape:	DR-G1130: 130ppm (Simplex) / 260ipm (Duplex)
		DR-G1100: 100ppm (Simplex) / 200ipm (Duplex)
Colour	Portrait:	DR-G1130: 100 ppm (Simplex) / 200 ipm (Duplex)
		DR-G1100: 75ppm (Simplex) / 150ipm (Duplex)
	Landscape:	DR-G1130: 130ppm (Simplex) / 200ipm (Duplex)
		DR-G1100: 100ppm (Simplex) / 200ipm (Duplex)
Interface	Hi-Speed USB 2.0	
Scanner driver	ISIS / TWAIN	
Useful functions	Job Function, Ultrasonic Double-Feed Detection, Staple Detection, Text Enhancement, Dropout and Color Enhancement, Auto Page Size Detection, 3-D Color Correction, Image Rotation, Skip Blank Page, Edge Emphasis, Moiré Removal, Prevent Bleed Through / Remove Background, Contrast Adjustment, Shading Correction, Brightness Adjustment, Deskew, Border Removal, Scanning Side Selection, Scan Area	

	Settings, Addon Settings, Text Orientation Recognition, Punch Hole Removal, Folio Scan, Unnecessary dots removal, Notch removal, Background Smoothing, Character Emphasis, Count Only Mode, Verify Scan, Rapid Recovery System, MultiStream™	
Power requirements	AC220–240V (50 / 60Hz)	
Power Consumption	220 – 240V:	94.3W (Scanning), 1.7W (Sleep mode)
Operating Environment	10 – 32.5°C	
	Humidity:	20 – 80% RH
Dimensions (W x D x H)	Feed trays closed:	480 x 535 x 315mm
Weight	Approx. 22.8kg	
Options / Consumables	Imprinter Unit, Barcode Module, Patchcode Decoder, Exchange Roller Kit, Separation Pad, Imprinter Ink Cartridges, Flatbed Scanner Units	

Specifications are subject to change without notice.

*1	Scanning speed may vary depending on PC environment, scanner settings, and other factors. Specifications are subject to change without notice.
----	--