

Specifications for imageRUNNER 2500W series

Device	imageRUNNER 2545W / 2535W / 2530W / 2525W / 2520W	
Type	Desktop (Reader Combined + Inner Output)	
Imaging System	Laser Dry Electrostatic Transfer System	
Memory	Standard:	256MB
	Maximum:	512MB
Network Interface	Ethernet (100Base-TX / 10Base-T), USB 2.0	
Warm Up Time	30 seconds maximum after powering ON	
	10 second maximum from the Sleep mode	
First Copy Output Time	imageRUNNER 2530W / 2525W / 2520W: 6.4 seconds or less	
	imageRUNNER 2545W / 2535W: 3.9 seconds or less	
Multiple Copies	1 to 999 sheets	
Magnification	25% to 400% (1% increment)	
Maximum Original Size	Max. A3	
Duplex	Standard	
Copy / Print Speed	A4:	imageRUNNER 2545W: 45ppm imageRUNNER 2535W: 35ppm imageRUNNER 2530W: 30ppm imageRUNNER 2525W: 25ppm imageRUNNER 2520W: 20ppm
	A3:	imageRUNNER 2545W: 22ppm imageRUNNER 2535W: 22ppm imageRUNNER 2530W: 15ppm imageRUNNER 2525W: 15ppm imageRUNNER 2520W: 15ppm
Resolution	Reading:	600 x 600dpi
	Writing:	1200 x 1200dpi
Paper Sources (80gsm)	Paper Cassette:	Standard: imageRUNNER 2520W: 250 sheets paper capacity imageRUNNER 2530W / 2525W: 250 + 550 sheets paper capacity imageRUNNER 2545W / 2535W: 2 x 550 sheets paper capacity
		Maximum: imageRUNNER 2520W: 250 + 3 x 550 sheets paper capacity imageRUNNER 2530W / 2525W: 250 + 3 x 550 sheets paper capacity imageRUNNER 2545W / 2535W: 4 x 550 sheets paper capacity
	Stack Bypass:	Standard: 100 sheets paper

		capacity
Acceptable Paper Weights	Paper Cassette:	64 to 90gsm
	Stack Bypass:	64 to 128gsm
Main Unit Dimensions (W x D x H)	imageRUNNER 2520W: 565 x 680 x 681mm (with the platen cover) 565 x 693 x 771mm (with the feeder) imageRUNNER 2530W / 2525W: 565 x 680 x 806mm (with the platen cover) 565 x 693 x 896mm (with the feeder) imageRUNNER 2545W / 2535W: 565 x 680 x 806mm (with the platen cover) 565 x 693 x 907mm (with the feeder)	
Weight	imageRUNNER 2520W: Approx. 50.5kg imageRUNNER 2530W / 2525W: Approx. 67.7kg imageRUNNER 2545W / 2535W: Approx 69.5kg	
Power Source	220 – 240V AC, 50 / 60Hz	
Maximum Power Consumption	imageRUNNER 2530W / 2525W / 2520W: Approx 1.542kW imageRUNNER 2545W / 2535W: Approx 1.827kW	
Toner Yield (6% Coverage)	imageRUNNER 2530W / 2525W / 2520W: Approx. 14,600 sheets (A4) imageRUNNER 2545W / 2535W: Approx 19,400 sheets (A4)	
Drum Yield	imageRUNNER 2530W/2525W/2520W: Approx. 132,000 sheets (A4) imageRUNNER 2545W/2535W: Approx 140,000 sheets (A4)	
Print Specification		
PDL	Standard:	UFR II LT
	Optional:	PCL 6, PS3
OS Compatibility	PCL	Windows 10 / 8.1 / 8 / 7 / Vista / Windows Server 2003 / Server 2003 R2 / Server 2008
	Adobe PostScript 3	Windows 10 / 8.1 / 8 / 7 / Vista / Windows Server 2003 / Server 2003 R2 / Server 2008 / Server 2008 R2 / Server 2012 R2 / Mac OS X10.5 or later
	UFR II	Windows 10 / 8.1 / 8 / 7 / Vista / Windows Server 2003 / Server 2003 R2 / Server 2008 / Server 2008 R2 / Server 2012 R2 / Mac OS X10.5 or later
Network ScanGear Specification		
Supported OS	Windows 8.1 / 8 / 7 / Vista / Windows Server 2003 / Server 2003 R2 / Server 2008 / Server 2008 R2 / Server 2012 R2	

Resolution	BW:	Up to 600 x 600dpi
	CL:	Up to 300 x 300dpi