

Specifications

Print Type	Line-type inkjet system	
Ink Type	Oil-based pigment ink (Cyan/Magenta/Yellow/Black)	
Print Resolution	Standard: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction)	
	Fine: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)	
Number of Gray Levels	For each CMYK color (11 gray levels)	
Data Processing Resolution	Standard: 300 dpi × 300 dpi	
	Fine: 600 dpi × 600 dpi	
	Line smoothing: 600 dpi × 600 dpi	
Warm-up Time	2 min. 30 sec. or less (at room temperature of 23°C (73.4°F))	
First Print Time*1	5 sec. or less (A4 long-edge feed)	
First Copy Time*1	7 sec. or less (A4 long-edge feed)	
Continuous Print Speed*2*3	A4 long-edge feed	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)
	Letter long-edge feed	Simplex: 120 ppm, Duplex: 60 sheets/minute (120 ppm)
	A4 short-edge feed	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)
	Letter short-edge feed	Simplex: 90 ppm, Duplex: 45 sheets/minute (90 ppm)
	B4(JIS) short-edge feed	Simplex: 76 ppm, Duplex: 34 sheets/minute (68 ppm)

	Legal short-edge feed	Simplex: 76 ppm, Duplex: 34 sheets/minute (68 ppm)
	A3 short-edge feed	Simplex: 66 ppm, Duplex: 32 sheets/minute (64 ppm)
	Ledger short-edge feed	Simplex: 65 ppm, Duplex: 32 sheets/minute (64 ppm)
Paper Size	Standard Tray	Maximum: 340 mm × 550 mm (13 3/8" × 21 5/8")*11
		Minimum: 90 mm × 148 mm (3 9/16" × 5 27/32")
Printable Area		Maximum: 310 mm × 544 mm (12 3/16" × 21 13/32")
Guaranteed Print Area*4		Standard: Margin width of 5 mm (7/32")
		Maximum: Margin width of 3 mm (1/8")
Paper Weight	Standard Tray	Simplex: 46 gsm to 210 gsm (12-lb bond to 56-lb bond)
		Duplex: 46 gsm to 210 gsm (12-lb bond to 56-lb bond) for A4 and Letter
		46 gsm to 104 gsm (12-lb bond to 28-lb bond) for Ledger, A3, Legal, and B4
Paper Tray Capacity	Standard Tray	Height up to 110 mm (4 5/16")
Output Tray Capacity	Standard	Height up to 56 mm (2 3/16")
Page Description Language		RISORINC/C IV
Supported Protocols		TCP/IP, HTTP, HTTPs, DHCP, ftp, lpr, IPP, SNMP, Port 9100 (RAW port), IPv4, IPv6, IPsec
Supported Operating Systems	Standard	Microsoft®: Windows Vista® (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows® 8.1

		(32-bit/64-bit), Windows® 10 (32-bit/64-bit),
		Windows Server® 2008 (32-bit/64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2016 (64-bit)
	Optional*5	Mac: Mac OS v10.8 (Mountain Lion), v10.9 (Mavericks), v10.10 (Yosemite), v10.11 (El Capitan), v10.12 (Sierra)
		Linux (compatible with PPD only)
Network Interface		Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T
Memory Capacity		4GB
Hard Disk*6	Capacity	500GB
	Available Space	Approx. 430GB
Operating System		Linux
Power Source		AC 100-240 V, 10.0-5.0 A, 50-60 Hz
Power Consumption		Maximum: 1,000 W
		Ready*7: 150 W or less
		Sleep*8: 4 W or less
		Stand-by: 0.5 W or less
Operating Noise		Max. 65 dB(A)A4 long-edge feed (Simplex) at the maximum print speed
Operating Environment		Temperature: 15°C to 30°C (59°F to 86°F)
		Humidity: 40% to 70% RH (non-condensing)

Dimensions (W × D × H)	In use: 1,030mm × 725 mm × 1,115 mm (40 19/32" × 28 9/16" × 43 29/32")
	With cover and tray closed: 775 mm × 705 mm × 970 mm (30 17/32" × 27 25/32" × 38 7/32")
Weight	Approx. 130 kg (286 lb)
Safety Information	IEC60950-1 compliant, Indoor, pollution degree 2*9, At altitudes of 2,000 m or lower
Required Space (W × D × H)*10	1,305 mm × 1,215 mm × 1,115 mm (51 13/32" × 47 27/32" × 43 29/32")

Note: Specifications are subject to change without notice.

*1: Within 10 minutes after the last print job.

*2: When using plain paper and recycled paper (85 gsm (23-lb bond)), and density setting Standard. Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].

*3: The continuous print speed varies depending on the type of optional output equipment connected.

*4: The margin when printing envelopes is 10 mm (3/8"). The guaranteed area when printing images is the area enclosed within 5 mm (7/32") of the edges of the paper.

*5: Optional PS Kit is required.

*6: One gigabyte (GB) is calculated as one billion bytes.

*7: Without printing and temperature adjustment operation.

*8: When setting [Power consumption (in sleep)] to [Low].

*9: The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

*10: With the front cover open and the operation panel in the upright position.

*11: When using duplex print: 340 mm × 460 mm (13 3/8" × 18 3/32")

RISO ComColor, and FORCEJET are trademarks or registered trademarks of RISO KAGAKU CORPORATION. Adobe and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Mac is a trademark of Apple Inc. Microsoft, Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.