

Printing




[Download Brochure](#)

General Specifications



Type	A4 Monochrome Multifunctional Device (Reader/Printer Desktop)
Copy/Print Speed	
A4	iR2206: 22ppm iR2006N: 20ppm iR2206N: 22ppm
A3	iR2206: 11ppm iR2006N: 10ppm iR2206N: 11ppm
Warm-Up Time (Time from device power on, until copy ready)	13 secs or less
Recovery from sleep mode	4.3secs

First Copy Time (A4)	7.4 secs
Memory	iR2206: 256 MB iR2006N & iR2206N: 512 MB
Dimensions (W x D x H)	iR2206: 622 x 589 x 502 iR2006N & iR2206N: 622 x 589 x 607mm (with ADF)
Weight	iR2206: Approximately 28.7 kg iR2006N & iR2206N: Approximately 35.5 kg (with ADF)
Installation Space (W x D)	920 x 589 mm (when multi purpose tray is extended)
Power Supply	iR2206: 220 to 240 V AC, 50/60 Hz, 2.4 A iR2006N & iR2206N: 220 to 240 V AC, 50/60 Hz, 2.7 A
Max Power Consumption	
Maximum Power Consumption:	1.5 kWh
When the machine is in the Sleep mode:	2 W
Toner Yield (A4, 6% coverage)	Approx 10,200 sheets (A4, 6% coverage)
Drum Yield	iR2206: Approx 66,000 sheets iR2006N: Approx 63,700 sheets iR2206N: Approx 66,000 sheets
Print Specifications 	
Print Resolution	600 x 600 dpi
Page Description Language(s)	iR2206: UFR II LT (Standard) iR2006N & iR2206N: UFR II LT (Standard), PCL6 (Optional)
Print OS Compatibility	Windows 10/8.1/7, Windows Server 2008/2008 R2/2012/2012 R2/ 2016, Mac OS X 10.9.5 or later
Interface	

Network iR2206: N/A
iR2006N & iR2206N: Ethernet
100Base-Tx/10Base-T (IEEE 802.3
compliant), WLAN IEEE 802.11b/g/n

Others (Local Print/Scan) USB2.0 x 1

Network Protocol iR2206: N/A
iR2006N & iR2206N:
TCP/IP (IPv4/IPv6), USB
Frame type: Ethernet II
Print applications:
LPD/Raw/IPP/IPPS/WSD/Mopria
/Google Cloud
Print/AirPrint/Windows10 Mobile
Print

Copy Specifications

Copy Resolution 600 x 600 dpi

Multiple Copies/Prints Up to 999 copies

Magnification 25% -400% (1% increment)

Send Specifications

Destination iR2206: N/A
iR2006N & iR2206N: Scan to Email
(SMTP), network folders (SMB)

Scan Speed (Simplex, A4, 200dpi) iR2206: N/A
iR2006N & iR2206N:
BW: 13 sheets/minute
CL: 6 sheets/minute

Address Book iR2206: N/A
iR2006N & iR2206N: LDAP
(5)/Local(104) /One-touch(4)

SEND Resolution iR2206: N/A
iR2006N & iR2206N: BW/CL 300 x 300
dpi

SEND File Format iR2206: N/A
iR2006N & iR2206N: PDF/Compact
PDF/JPEG/ TIFF

Scan Specifications



Destination	MF Scan Utility, application compatible with TWAIN/WIA
Supported Protocol	TCP/IP, USB
Scan Speed (Simplex, A4, 300 dpi)	BW: 23 sheets/minute CL: 12 sheets/minute
Scan Resolution	BW: 600 x 600 dpi CL: 300 x 600 dpi
Scan File Format	TIFF/JPEG/PNG/PDF(Compact, Searchable)/PDF(Divided into Single-Page Files)
Scan OS Compatibility	Windows 10/8.1/7, Windows Server2008/2008 R2/2012/2012 R2/2016, Mac OS X 10.9.5 or later

Security



Authentication	iR2206: N/A iR2006N & iR2206N: Department ID management (Max: 100 IDs)
Network	iR2206: N/A iR2006N & iR2206N: Standard: IP/Mac Address Filtering, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
Document	iR2206: N/A iR2006N & iR2206N: Secure Print (Max: 100 IDs)

Paper Handling



Paper Sizes

Cassette 1	A3,B4,A4R,A4,B5,B5R,A5R,India-LGL, FOOLSCAP
------------	---

Cassette 2	iR2206: N/A iR2006N & iR2206N: A3,B4,A4R,A4,A5,B5,B5R
Multi Purpose Tray	A3,B4,A4R,A4,B5,B5R,A5,A5R,India-LGL, FOOLSCAP, Envelope (COM 10, Monarch, ISO-C5, DL)

Paper Input Capacity (Standard)

Cassette 1	250 sheets (80 gsm)
Multi Purpose Tray	80 sheets (80 gsm)

Paper Input Capacity (Optional)

Cassette 2*	iR2206: N/A iR2006N & iR2206N: 250 sheets (80 gsm)
-------------	---

Paper Specification

Cassette	Weight: 64 - 90 gsm Type: Plain (64 to 90gsm), Recycled (65 to 80gsm), Colour (64 to 80gsm), Pre-punched (75 to 80 gsm)
Multi Purpose Tray	Weight:60-128 gsm Type: Plain (64 to 90gsm), Heavy 1 (91 to 105 gsm), Heavy 2 (106 to 128gsm), Recycled (65 to 80gsm), Colour (64 to 80gsm), Pre-punched (75 to 80 gsm), Bond (75 to 90 gsm), Transparency, Label, Envelope)

Optional Accessories



Duplex Automatic Document Feeder - AY1*

Type	iR2206: N/A iR2006N & iR2206N: Automatic Document Feeder
Size of Originals	iR2206: N/A iR2006N & iR2206N: A3, B4, A4, A4R, B5, B5R, A5, A5R, FOOLSCAP, India LGL

Paper Weight	iR2206: N/A iR2006N & iR2206N: When scanning continuously: 52 to 105g/m ² When scanning a single original: 37 to 128 g/m ²
Max. Number of Originals	iR2206: N/A iR2006N & iR2206N: 50 sheets (A4, 80 gsm)
Scanning Speed (Simplex)	
Copying (A4 in BW at 600 dpi)	iR2206: N/A iR2006N: 20ipm iR2206N: 22ipm
Scanning (A4 in BW 300 dpi)	iR2206: N/A iR2006N & iR2206N: 23 ipm
Dimensions (W x D x H)	iR2206: N/A iR2006N & iR2206N: 565 x 520.5 x 126 mm
Weight	iR2206: N/A iR2006N & iR2206N: Approximately 7.0 kg
Cassette Feeding Module- AD1	
Paper Sizes	iR2206: N/A iR2006N & iR2206N: A3,B4,A4R,A4,A5,B5,B5R
Paper Capacity	iR2206: N/A iR2006N & iR2206N: 250 sheets (80 gsm)
Power Source	iR2206: N/A iR2006N & iR2206N: From main unit
Dimensions (W x D x H)	iR2206: N/A iR2006N & iR2206N: 579 x 575 x 116 mm
Weight	iR2206: N/A iR2006N & iR2206N: Approx. 5.75 kg
Other Optional Accessories and Supplies	

Duplex Unit-C1*, Platen Cover Type X*, FL Cassette-BB1*, Heater Kit-M2,
Cassette Heater Unit-40, NPG-59 Drum Unit, NPG-59 Black Toner.

* Available for iR2206N/2006N only.

-
- All prices above are recommended retail price in INR, unless otherwise stated.
-

Copyright © 2019 Canon India Pvt Ltd. All rights reserved.