

SPECIFICATIONS

Main unit

Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control panel	Standard: 17.78 cm (7 inch) TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Interface Connection	Network: 1000Base-T / 100Base-TX / 10Base-T, Wireless LAN (IEEE 802.11 b / g / n) Others: USB 2.0 (Host) x3, USB 2.0 (Device) x1
Print / Copy speed	iR 2645: 45 pages/min (A4), 22 pages/min (A3) iR 2630 / 2625: 30 pages/min (A4), 15 pages/min (A3) iR 2625: 25 pages/min (A4), 15 pages/min (A3)
Memory media	Standard: USB memory
Paper supply capacity (A4, 80g/m² (gsm))	Standard: 1 200 sheets Maximum: 2 300 sheets (with Cassette Feeding Unit-AN1)
Paper output capacity (A4, 80g/m² (gsm))	Standard: 250 sheets Maximum: 545 sheets (with Inner Finisher-J1)
Supported media weights	Paper cassettes (1 / 2): 60 to 128g/m ² (gsm) Multi-purpose tray: 52 to 220g/m ² (gsm) (Thin vertical grain paper feed only: 52 to 59g/m ² (gsm)) Duplex: 60 to 105g/m ² (gsm)
Warm-up time (Quick start mode: ON)	From power-on: 12s or less* From sleep mode: 10s or less *Time from power-on, until copy ready
Dimensions (W x D x H)	iR 2645: 586.0 x 709.0 x 926.0 mm (with DADF-BA1) iR 2630 / 2625: 586.0 x 713.0 x 912.0 mm (with DADF-AZ1) iR 2625: 586.0 x 700.0 x 818.0 mm (with Platen Cover type Z)
Weight	Standard: iR 2645: Approximately 68.3 kg without toner iR 2630 / 2625: Approximately 66.8 kg without toner
Power source	220-240 V, 5.2 Amp
Power consumption	Maximum: Approximately 1 500W Standby: Approximately 20W Sleep mode: Approximately 0.6W

Print specifications

Print resolution	1 200 x 1 200dpi
Page description language	Standard: UFR II Optional: Genuine Adobe® PostScript® 3™, PCL 6
Operating system	UFR II: Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) PCL (Optional): Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019 PS: Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) PPD: Windows® 7 / 8.1 / 10, MAC OS X (10.9 or later)

Copy specifications

First-Copy-Out Time (A4)	iR 2645: Approximately 3.9s or less iR 2630 / 2625: Approximately 5.9s or less
Copy resolution	Reading: 600 x 600dpi Printing: Up to 1 200 x 1 200dpi
Multiple copies	Up to 9 999 copies

Send specifications

Destination	Email / I-Fax (SMTP), SMB, FTP, WebDAV, Super G3 FAX (Optional)
Address book	LDAP (2 000) / Local (1 600) / One-touch (200)
Send resolution	Push: 600 x 600dpi Pull: 600 x 600dpi, 400 x 400dpi, 300 x 300dpi, 200 x 200dpi, 150 x 150dpi, 75 x 75dpi
Communication protocol	File: FTP (TCP / IP), SMB (TCP / IP), WebDAV Email / I-Fax: SMTP (Send), POP3 (Receive)
File format	Standard: TIFF (MIR), JPEG®, PDF (Compact, PDF A / 1-b, Encrypted), XPS (Compact), PDF / XPS (Device signature) Optional: PDF (Trace & smooth), PDF / XPS (User signature, Searchable), Office Open XML (PowerPoint, Word)

*Single page only

To arrange for a demonstration, simply contact:

CANON INDIA PVT. LTD.
7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

Disclaimer: This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. Other names may be the trademarks of their respective owners.

uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte. Ltd.



Scan specifications

Selectable type (Optional)	iR 2645: Document Feeder (DADF-BA1) or Platen Cover Type Y iR 2630 / 2625: Document Feeder (DADF-AZ1) or Platen Cover Type Z
Document feeder paper capacity 80g/m² (gsm)	DADF-BA1: 100 sheets DADF-AZ1: 50 sheets
Scan speed (BW / CL; A4)	DADF-BA1: 1-sided scanning: 55 / 55 images/min (BW / CL; 300 dpi), 45 (BW; 600dpi) 2-sided scanning: 27.5 / 27.5 images/min (BW / CL; 300dpi), 22.5 (BW; 600 dpi) DADF-AZ1: 1-sided scanning: 35 / 25 images/min (BW / CL; 300dpi), 25 (BW; 600dpi) 2-sided scanning: 12 / 8 images/min (BW / CL; 300dpi), 9 (BW; 600dpi)
Scan resolution	Copy: 600 x 600dpi Send: (Push) Up to 600 x 600dpi, (Pull) Up to 600 x 600dpi Fax: Up to 600 x 600dpi
Pull scan specifications	Colour Network ScanGear2 for both TWIN and WIA

Fax specifications

Optional / standard	Optional on all models
Maximum number of connection lines	1
Modem speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression method	MH, MR, MMR, JBIG
Resolution	400 x 400dpi (Ultrafine), 200 x 400dpi (Superfine), 200 x 200dpi (Fine / Photo), 200 x 100dpi (Normal)
Fax memory	Up to 30 000 pages
Speed dials	Max. 200
Group dials / destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes

Security specifications

Authentication	Standard: uniFLOW Online Express, User Authentication, Department ID Authentication, Access Management System, Picture Login Optional: My Print Anywhere secure print (Requires uniFLOW)
Network	Standard: IP / Mac address filtering, IPSEC, TLS encrypted communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP authentication, POP authentication before SMTP, S/MIME
Document	Standard: Secure print, Encrypted PDF, Encrypted secure print, Device signature Optional: User signature

Consumables

Toner cartridge/s	NPG-84 Toner Black
Toner (Estimated yield @ 6% coverage)	Black: 30 000 impressions (A4)

Paper supply options

Cassette Feeding Unit-AN1	Paper Capacity: 550 sheets x 2 (80g/m ²) Paper Type: Thin, Plain, Thick, Colour, Recycled, Pre-punched Paper Size: A3, A4, A4R, A5R, B4, B5, B5R Custom size: 139.7 x 182.0 to 297.0 x 431.8 mm Paper Weight: 60 to 128g/m ² (gsm) Power Source: From the main unit Dimensions (W x D x H): 565.0 x 650.0 x 248.0 mm (attached to the main unit) Weight: Approximately 23.5 kg
----------------------------------	---

Other accessories and supplies

Envelope Feeder Attachment-D1, Inner 2Way Tray-L1, Inner Finisher-J1, Copy Card Reader-F1, IC Card Reader Box-C2, Copy Card Reader Attachment-H3, Utility Tray-B1, Document Tray-J1, Platen Cover Type Z, Platen Cover Type Y, DADF-AZ1, DADF-BA1, PCL International Font Set-A1, PS Printer Kit-B1, Universal Send Digital User Signature Kit-C1, Universal Send Advanced Feature Set-H1, Barcode Printing Kit-D1, Copy Control Interface Kit-D1, Super G3 Fax Board-AV2, Remote Fax Kit-A1, ADF Access Handle-A1, Staple-P1

imageRUNNER 2645 / 2630 / 2625

imageRUNNER SERIES REDEFINED

Transform The Way You Work



Print Up to 45 pages/min

17.78 cm (7 inch) Colour Touch Panel

Mobile Print Ready

DEALER'S STAMP

0121BN460 © 2020 Canon India Pte. Ltd.
All rights reserved. Printed In India.

Business Can Be Simple



THE NEW iR 2600 SERIES GREATER PEACE OF MIND WITH PERFORMANCE RELIABILITY



Highly robust machine



Enhanced functionalities



Improved performance



IMPROVED CONNECTIVITY BETWEEN OFFICE IT EQUIPMENT



Wireless LAN router (Access point)



Computer & mobile devices



Multi-functional devices



BOOSTED PRODUCTIVITY WITH HIGHER USABILITY



1 Higher operability with 17.78 cm (7 inch) colour touch panel

- Navigate easily with touch operations similar to a smartphone, such as flick, drag-and-drop.

2 Smart and sophisticated design

- Save time with quick selection and execution of last 10 used functions.

3 Fully customisable functions

- Personalise print functions and individual user settings to simplify workflows and increase productivity.

A POWERFUL AND SECURE MULTI-FUNCTIONAL PRINTER FOR YOUR BUSINESS



Provide security measures based on your needs

- Enjoy greater document security with Encrypted PDF, Device signature PDF and optional User signature PDF.
- Secure office environment with available network security functions such as SNMP v3, IEEE 802.1x and dual network.



Manage your prints with uniFLOW Online Express

- Prevent unauthorised prints by limiting access with authentication.
- Track usage and manage costs with an intuitive dashboard supported by personalised widgets.
- Prevent unintended or incorrect outputs when paired with forced-hold print feature, to temporarily hold documents in each device.



Convert paper files to electronic data easily

- Convert paper originals into electronic data, including Microsoft PowerPoint* (.pptx format) and Word* (.docx format) so work can be done with an easily editable format.
- Retain document style while creating text searchable* documents, reducing the need for manual input.

*Optional



MOBILE PRINTING

iR 2600 series supports a wide range of mobile applications, ranging from Canon PRINT Business, Apple® AirPrint®, Google Cloud Print™, Mopria® and Canon Print Service. Printing or scanning from a mobile device has never been easier.