

# SPECIFICATIONS

## Main unit

<b>Machine type</b>	A3 Monochrome Laser Multifunctional
<b>Core functions</b>	Print, Copy, Scan, Send and Optional Fax
<b>Control panel</b>	<b>Standard:</b> 17.78 cm (7 inch) TFT LCD WVGA Colour Touch panel
<b>Memory</b>	<b>Standard:</b> 2.0GB RAM
<b>Interface Connection</b>	<b>Network:</b> 1000Base-T / 100Base-TX / 10Base-T, Wireless LAN (IEEE 802.11 b / g / n) <b>Others:</b> USB 2.0 (Host) x3, USB 2.0 (Device) x1
<b>Print / Copy speed</b>	<b>iR 2645:</b> 45 pages/min (A4), 22 pages/min (A3) <b>iR 2630 / 2625:</b> 30 pages/min (A4), 15 pages/min (A3) <b>iR 2625:</b> 25 pages/min (A4), 15 pages/min (A3)
<b>Memory media</b>	<b>Standard:</b> USB memory
<b>Paper supply capacity (A4, 80g/m<sup>2</sup> (gsm))</b>	<b>Standard:</b> 1 200 sheets <b>Maximum:</b> 2 300 sheets (with Cassette Feeding Unit-AN1)
<b>Paper output capacity (A4, 80g/m<sup>2</sup> (gsm))</b>	<b>Standard:</b> 250 sheets <b>Maximum:</b> 545 sheets (with Inner Finisher-J1)
<b>Supported media weights</b>	<b>Paper cassettes (1 / 2):</b> 60 to 128g/m <sup>2</sup> (gsm) <b>Multi-purpose tray:</b> 52 to 220g/m <sup>2</sup> (gsm) (Thin vertical grain paper feed only: 52 to 59g/m <sup>2</sup> (gsm)) <b>Duplex:</b> 60 to 105g/m <sup>2</sup> (gsm)
<b>Warm-up time (Quick start mode: ON)</b>	<b>From power-on:</b> 12s or less* <b>From sleep mode:</b> 10s or less  *Time from power-on, until copy ready
<b>Dimensions (W x D x H)</b>	<b>iR 2645:</b> 586.0 x 709.0 x 926.0 mm (with DADF-BA1) <b>iR 2630 / 2625:</b> 586.0 x 713.0 x 912.0 mm (with DADF-AZ1) <b>iR 2625:</b> 586.0 x 700.0 x 818.0 mm (with Platen Cover type Z)
<b>Weight</b>	<b>Standard:</b> <b>iR 2645:</b> Approximately 68.3 kg without toner <b>iR 2630 / 2625:</b> Approximately 66.8 kg without toner
<b>Power source</b>	220-240 V, 5.2 Amp
<b>Power consumption</b>	<b>Maximum:</b> Approximately 1 500W <b>Standby:</b> Approximately 20W <b>Sleep mode:</b> Approximately 0.6W

## Print specifications

<b>Print resolution</b>	1 200 x 1 200dpi
<b>Page description language</b>	<b>Standard:</b> UFR II <b>Optional:</b> Genuine Adobe® PostScript® 3™, PCL 6
<b>Operating system</b>	<b>UFR II:</b> Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) <b>PCL (Optional):</b> Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019 <b>PS:</b> Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) <b>PPD:</b> Windows® 7 / 8.1 / 10, MAC OS X (10.9 or later)

## Copy specifications

<b>First-Copy-Out Time (A4)</b>	<b>iR 2645:</b> Approximately 3.9s or less <b>iR 2630 / 2625:</b> Approximately 5.9s or less
<b>Copy resolution</b>	<b>Reading:</b> 600 x 600dpi <b>Printing:</b> Up to 1 200 x 1 200dpi
<b>Multiple copies</b>	Up to 9 999 copies

## Send specifications

<b>Destination</b>	Email / I-Fax (SMTP), SMB, FTP, WebDAV, Super G3 FAX (Optional)
<b>Address book</b>	LDAP (2 000) / Local (1 600) / One-touch (200)
<b>Send resolution</b>	<b>Push:</b> 600 x 600dpi <b>Pull:</b> 600 x 600dpi, 400 x 400dpi, 300 x 300dpi, 200 x 200dpi, 150 x 150dpi, 75 x 75dpi
<b>Communication protocol</b>	<b>File:</b> FTP (TCP / IP), SMB (TCP / IP), WebDAV <b>Email / I-Fax:</b> SMTP (Send), POP3 (Receive)
<b>File format</b>	<b>Standard:</b> TIFF (MIR), JPEG®, PDF (Compact, PDF A / 1-b, Encrypted), XPS (Compact), PDF / XPS (Device signature) <b>Optional:</b> PDF (Trace & smooth), PDF / XPS (User signature, Searchable), Office: Open XML (PowerPoint, Word)

\*Single page only

To arrange for a demonstration, simply contact:

**CANON INDIA PVT. LTD.**  
7<sup>th</sup> Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002  
Ph: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

**Disclaimer:** This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. Other names may be the trademarks of their respective owners.

uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte. Ltd.



## Scan specifications

<b>Selectable type (Optional)</b>	<b>iR 2645:</b> Document Feeder (DADF-BA1) or Platen Cover Type Y <b>iR 2630 / 2625:</b> Document Feeder (DADF-AZ1) or Platen Cover Type Z
<b>Document feeder paper capacity 80g/m<sup>2</sup> (gsm)</b>	<b>DADF-BA1:</b> 100 sheets <b>DADF-AZ1:</b> 50 sheets
<b>Scan speed (BW / CL; A4)</b>	<b>DADF-BA1:</b> 1-sided scanning: 55 / 55 images/min (BW / CL; 300 dpi), 45 (BW; 600dpi) 2-sided scanning: 27.5 / 27.5 images/min (BW / CL; 300dpi), 22.5 (BW; 600 dpi) <b>DADF-AZ1:</b> 1-sided scanning: 35 / 25 images/min (BW / CL; 300dpi), 25 (BW; 600dpi) 2-sided scanning: 12 / 8 images/min (BW / CL; 300dpi), 9 (BW; 600dpi)
<b>Scan resolution</b>	<b>Copy:</b> 600 x 600dpi <b>Send:</b> (Push) Up to 600 x 600dpi, (Pull) Up to 600 x 600dpi <b>Fax:</b> Up to 600 x 600dpi
<b>Pull scan specifications</b>	Colour Network ScanGear2 for both TWIN and WIA

## Fax specifications

<b>Optional / standard</b>	Optional on all models
<b>Maximum number of connection lines</b>	1
<b>Modem speed</b>	<b>Super G3:</b> 33.6 kbps <b>G3:</b> 14.4 kbps
<b>Compression method</b>	MH, MR, MMR, JBIG
<b>Resolution</b>	400 x 400dpi (Ultrafine), 200 x 400dpi (Superfine), 200 x 200dpi (Fine / Photo), 200 x 100dpi (Normal)
<b>Fax memory</b>	Up to 30 000 pages
<b>Speed dials</b>	Max. 200
<b>Group dials / destinations</b>	Max. 199 dials
<b>Sequential broadcast</b>	Max. 256 addresses
<b>Memory backup</b>	Yes

## Security specifications

<b>Authentication</b>	<b>Standard:</b> uniFLOW Online Express, User Authentication, Department ID Authentication, Access Management System, Picture Login <b>Optional:</b> My Print Anywhere secure print (Requires uniFLOW)
<b>Network</b>	<b>Standard:</b> IP / Mac address filtering, IPSEC, TLS encrypted communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP authentication, POP authentication before SMTP, S/MIME
<b>Document</b>	<b>Standard:</b> Secure print, Encrypted PDF, Encrypted secure print, Device signature <b>Optional:</b> User signature

## Consumables

<b>Toner cartridge/s</b>	NPG-84 Toner Black
<b>Toner (Estimated yield @ 6% coverage)</b>	<b>Black:</b> 30 000 impressions (A4)

## Paper supply options

<b>Cassette Feeding Unit-AN1</b>	<b>Paper Capacity:</b> 550 sheets x 2 (80g/m <sup>2</sup> ) <b>Paper Type:</b> Thin, Plain, Thick, Colour, Recycled, Pre-punched <b>Paper Size:</b> A3, A4, A4R, A5R, B4, B5, B5R Custom size: 139.7 x 182.0 to 297.0 x 431.8 mm <b>Paper Weight:</b> 60 to 128g/m <sup>2</sup> (gsm) <b>Power Source:</b> From the main unit <b>Dimensions (W x D x H):</b> 565.0 x 650.0 x 248.0 mm (attached to the main unit) <b>Weight:</b> Approximately 23.5 kg
----------------------------------	---

## Other accessories and supplies

Envelope Feeder Attachment-D1, Inner 2Way Tray-L1, Inner Finisher-J1, Copy Card Reader-F1, IC Card Reader Box-C2, Copy Card Reader Attachment-H3, Utility Tray-B1, Document Tray-J1, Platen Cover Type Z, Platen Cover Type Y, DADF-AZ1, DADF-BA1, PCL International Font Set-A1, PS Printer Kit-B1, Universal Send Digital User Signature Kit-C1, Universal Send Advanced Feature Set-H1, Barcode Printing Kit-D1, Copy Control Interface Kit-D1, Super G3 Fax Board-AV2, Remote Fax Kit-A1, ADF Access Handle-A1, Staple-P1

## imageRUNNER 2645 / 2630 / 2625

# imageRUNNER SERIES REDEFINED

Transform The Way You Work



Print Up to 45 pages/min

17.78 cm (7 inch) Colour Touch Panel

Mobile Print Ready

DEALER'S STAMP

01BHN60 © 2020 Canon India Pte. Ltd.  
All rights reserved. Printed In India.

Business Can Be Simple



## THE NEW iR 2600 SERIES GREATER PEACE OF MIND WITH PERFORMANCE RELIABILITY



Highly robust machine



Enhanced functionalities



Improved performance



## IMPROVED CONNECTIVITY BETWEEN OFFICE IT EQUIPMENT



Wireless LAN router (Access point)



Computer & mobile devices



Multi-functional devices



## BOOSTED PRODUCTIVITY WITH HIGHER USABILITY



### 1 Higher operability with 17.78 cm (7 inch) colour touch panel

- Navigate easily with touch operations similar to a smartphone, such as flick, drag-and-drop.

### 2 Smart and sophisticated design

- Save time with quick selection and execution of last 10 used functions.

### 3 Fully customisable functions

- Personalise print functions and individual user settings to simplify workflows and increase productivity.

## A POWERFUL AND SECURE MULTI-FUNCTIONAL PRINTER FOR YOUR BUSINESS



### Provide security measures based on your needs

- Enjoy greater document security with Encrypted PDF, Device signature PDF and optional User signature PDF.
- Secure office environment with available network security functions such as SNMP v3, IEEE 802.1x and dual network.



### Manage your prints with uniFLOW Online Express

- Prevent unauthorised prints by limiting access with authentication.
- Track usage and manage costs with an intuitive dashboard supported by personalised widgets.
- Prevent unintended or incorrect outputs when paired with forced-hold print feature, to temporarily hold documents in each device.



### Convert paper files to electronic data easily

- Convert paper originals into electronic data, including Microsoft PowerPoint\* (.pptx format) and Word\* (.docx format) so work can be done with an easily editable format.
- Retain document style while creating text searchable\* documents, reducing the need for manual input.

\*Optional



## MOBILE PRINTING

iR 2600 series supports a wide range of mobile applications, ranging from Canon PRINT Business, Apple® AirPrint®, Google Cloud Print™, Mopria® and Canon Print Service. Printing or scanning from a mobile device has never been easier.