

# Canon

Delighting You Always

**imageRUNNER** | **4751** **4735**  
**ADVANCE DX** | **4745** **4725**

## Robust and reliable, with outstanding performance

The imageRUNNER ADVANCE DX 4700 series offers a wide range of solution for the modern day office in its compact design. This highly dependable series is ideal to fulfill daily office tasks.



### WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Industry leading Single-Pass document feeder option to allow up to 270 images/min scanning, supports paper skew prevention and comes with advanced anti-dust/streak measures.
- Advance personalisation enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

### COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Seamless integration with output management solutions, such as uniFLOW or uniFLOW Online Express for detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

**Business Can Be Simple**

## QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies contribute to high-quality output to meet the needs of busy department.
- State-of-the-art imaging technologies and toner allow for consistent images in rich black-and-white tones and 1200dpi print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Optional PCL and optional Adobe® PostScript® 3™ print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

## SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.9W in sleep mode.

## SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- Ensure device is safe from unknown firmware installation with system verification at startup.
- Integrate with third-party solutions for complete monitoring protection.

# MACHINE SPECIFICATION

## MAIN UNIT

**Type**  
A3 Monochrome Laser Multifunctional

**Core Function**  
Print, Copy, Scan, Send, Store and Optional Fax

**Processor**  
Canon Dual Custom Processor (Shared)

**Control Panel**  
Standard: 25.65 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel

**Memory**  
Standard : 3.0GB RAM

**Hard Disk drive**  
Standard\* : 320GB (Available Disk Space: 250GB)  
Maximum : 1TB  
\* A different initial HDD may be used.

**Mirroring Hard Disk Drive:** Optional

**Interface Connection**  
Standard: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

**Others** Standard: USB 2.0 x 1 (Host), USB 3.0 x 1 (Host),  
USB 2.0 x 1 (Device)  
Optional : Serial Interface, Copy Control Interface

**Paper Supply Capacity A4, 80g/m<sup>2</sup> (gsm)**  
Standard : 1200 sheets (2x 550-sheet cassette,  
1x 100-sheet multi-purpose tray)  
Maximum : 6350 sheets (with High Capacity Cassette  
Feeding Unit-B1 and Paper Deck Unit-F1)

**Paper Output Capacity A4, 80g/m<sup>2</sup> (gsm)**  
Standard : 250 Sheets  
Maximum : 3350 Sheets (with Buffer Pass-N1 +  
Staple Finisher-Y1 or Booklet Finisher-Y1)

**Finishing Capabilities**  
Standard : Collate, Group  
With options : Collate, Group, Offset, Staple, Saddle Stitch,  
Hole Punch, ECO Staple, Staple-On-Demand

**Supported Media Types**  
**Multi-Purpose Tray:**  
Thin, Plain, Heavy, Colour, Recycled, Pre-punched,  
Transparency, Tracing, Label, Bond, Envelope  
**Paper Cassette (1/2):**  
Thin, Plain, Heavy, Colour, Recycled, Pre-punched

**Supported Media Sizes**  
**Multi-Purpose Tray:**  
Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,  
Foolscap, India Legal, F4A  
Custom Size: 98.0 x 148.0 mm to 297.0 x 431.8 mm  
Free size: 98.0 x 148.0 mm to 297.0 x 431.8 mm  
Envelope: COM10 No.10, Monarch, DL, ISO-C5  
Envelope custom size: 98.0 x 148.0 mm to 297.0 x 431.8 mm  
**Paper Cassette 1:**  
Standard size : A4, A4R, A5R, B4, B5, B5R, Foolscap,  
India Legal, F4A  
Custom size : 139.7 x 182.0 mm to 297.0 x 390.0 mm

**Paper Cassette 2:**  
Standard size: A3, A4, A4R, A5R, B4, B5, B5R, Foolscap,  
India Legal, F4A  
Custom size : 139.7 x 182.0 mm to 297.0 x 431.8 mm  
Envelope\* : COM10 No.10, Monarch, DL, ISO-C5  
\* Envelope Feeder Attachment-D1 is required.

**Supported Media Weights**  
Multi-purpose tray : 52 to 220g/m<sup>2</sup> (gsm)  
(Thin 52 to 59g/m<sup>2</sup> (gsm); vertical grain paper feed only)  
Paper Cassette (1/2) : 60 to 220g/m<sup>2</sup> (gsm)  
Duplex : 60 to 105g/m<sup>2</sup> (gsm)

**Warm-up Time**  
Quick Startup Mode : 4s or less\*  
From Sleep Mode : 10s or Less  
From Power On : 24s or Less\*  
+ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.  
\* Time from device power-on, until copy ready (not print reservation)

**Dimensions (W x D x H)**  
With Platen Cover-Y2 : 608.0 x 713.0 x 822.0 mm  
With Single Pass DADF-C1 : 608.0 x 722.0 x 932.0 mm  
With DADF-BA1 : 608.0 x 719.0 x 926.0 mm

**Installation Space (W x D)**  
Basic: 1116.0 x 1160.0 mm (with Platen Cover Type Y2 +  
Multi-purpose tray open/extension tray extended +  
Paper Cassette open)  
1116.0 x 1169.0 mm (with Single Pass DADF-C1 +  
Multi-purpose tray open/extension tray extended +  
Paper Cassette open)  
1116.0 x 1166.0 mm (with DADF-BA1 + Multi-purpose tray  
open/extension tray extended + Paper Cassette open)

**Fully Configured:**  
1811.0 x 1169.0 mm (with Single Pass DADF-C1 + Paper  
Deck Unit-F1 + Booklet Finisher-Y1 with extension tray  
extended and Saddle unit drawn)  
1811.0 x 1166.0 mm (with DADF-BA1 + Paper Deck Unit F1  
+ Booklet Finisher-Y1 with extension tray extended and  
Saddle unit drawn)

**Weight**  
**iR-ADV DX 4751/4745/4735 :**  
With Platen Cover-Y2 : Approx. 76.1 kg including toner  
With Single Pass DADF-C1 : Approx. 89.0 kg including toner  
With DADF-BA1 : Approx. 82.5 kg including toner

**iR-ADV DX 4725:**  
With Platen Cover-Y2 : Approx. 75.0 kg including toner  
With Single Pass DADF-C1 : Approx. 87.9 kg including toner  
With DADF-BA1 : Approx. 81.4 kg including toner

## Printing Specifications

**Print Speed**  
iR-ADV DX 4751 : Up to 51 pages/min (A4), Up to 37 pages/min (A4R),  
Up to 25 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4745 : Up to 45 pages/min (A4), Up to 32 pages/min (A4R),  
Up to 22 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4735 : Up to 35 pages/min (A4), Up to 32 pages/min (A4R),  
Up to 22 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4725 : Up to 25 pages/min (A4), Up to 17 pages/min (A4R),  
Up to 15 pages/min (A3), Up to 17 pages/min (A5R)

**Print Resolution:** 1200 x 1200dpi

**Page Description Languages**  
Standard : UFR II  
Optional : Adobe® PostScript® 3™, PCL 6

**Direct Print**  
Supported file types: PDF, EPS, TIFF/JPEG, and XPS

**Printing From Mobile and Cloud**  
AirPrint, Mopria, Google Cloud Print, Canon Print Business  
and uniFLOW Online

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements.

Please contact your sales representative for further information

**Fonts**  
PS fonts: 136 Roman  
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT /K/S/T<sup>1</sup> (Japanese, Korean,  
Simplified and Traditional Chinese),  
Barcode fonts<sup>2</sup>

<sup>1</sup> Requires optional PCL INTERNATIONAL FONT SET-A1  
<sup>2</sup> Require optional BARCODE PRINTING KIT-D1

**Operating System**  
UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019  
PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)

## Copy Specifications

iR-ADV DX 4751 : Up to 51 pages/min (A4), Up to 37 pages/min (A4R),  
Up to 25 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4745 : Up to 45 pages/min (A4), Up to 32 pages/min (A4R),  
Up to 22 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4735 : Up to 35 pages/min (A4), Up to 32 pages/min (A4R),  
Up to 22 pages/min (A3), Up to 20 pages/min (A5R)  
iR-ADV DX 4725 : Up to 25 pages/min (A4), Up to 17 pages/min (A4R),  
Up to 15 pages/min (A3), Up to 17 pages/min (A5R)

**First-Copy-Out Time (A4)**  
iR-ADV DX 4751 : Approx. 3.7s or less  
iR-ADV DX 4745/4735 : Approx. 3.8s or less  
iR-ADV DX 4725 : Approx. 5.2s or less

**Copy Resolution** 600 x 600dpi  
**Multiple Copies** Up to 9 999 copies  
**Copy Density** Automatic or Manual (9 Levels)

**Magnification**  
Variable zoom: 25% - 400% (1% Increments)  
Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%,  
86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

## Scan Specifications

Type	
Standard	: Colour Flatbed Scan Unit
Optional	: Platen Cover Type-Y2, Single Pass DADF-C1* or DADF-BA1 [2-sided to 2-sided (Automatic with DADF)]

\* Detect Feeder Multi Sheet Feed is supported.

**Document Feeder Paper Capacity 80g/m<sup>2</sup> (gsm)**  
Single Pass DADF-C1 : up to 200 sheets  
DADF-BA1 : up to 100 sheets

**Acceptable Originals and Weights**  
Platen: Sheet, Book, and 3-Dimensional objects

Document Feeder media weight:  
SINGLE PASS DADF-C1\*:  
1-sided scanning : 38 to 220g/m<sup>2</sup> (gsm) (BW, CL)  
2-sided scanning : 38 to 220g/m<sup>2</sup> (gsm) (BW, CL)

\*Acceptable weights of A6R or smaller is 50 to 220g/m<sup>2</sup> (gsm).

DADF-BA1:  
1-sided scanning : 38 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)  
2-sided scanning : 50 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)

**Supported Media Sizes**  
Platen: max. scanning size: up to 297.0 x 431.8 mm  
Document Feeder media size:  
Single Pass DADF-C1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,  
Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm  
DADF-BA1: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6,  
Custom size: 139.7 x 128 mm to 297.0 x 431.8 mm

**Scan Speed (BW/CL; A4)**  
Single Pass DADF-C1:  
1-sided Scanning : 135/135 images/min (300 x 300dpi, send),  
80/80 images/min (600 x 600dpi, copy)  
2-sided Scanning : 270/270 images/min (300 x 300dpi, send),  
160/90 images/min (600 x 600dpi, copy)  
DADF-BA1:  
1-sided Scanning : 70/70 images/min (300 x 300dpi, send),  
51/51 images/min (600 x 600dpi, copy)  
2-sided Scanning : 35/35 images/min (300 x 300dpi, send),  
25.5/25.5 images/min (600 x 600dpi, copy)

**Scan Resolution**  
Scan for Copy : 600 x 600dpi  
Scan for Send : (Push) 600 x 600dpi (SMB/FTP/WebDAV/  
iFAX), (Pull) 600 x 600dpi  
Scan for Fax : 600 x 600dpi

**Pull Scan Spec**  
Colour Network ScanGear2. For both TWAIN and WIA  
Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016

## Send Specifications

**Destination**  
Standard : E-mail/Internet FAX (SMTP), SMB 3.0, FTP,  
WebDAV, Mail Box  
Optional : Super G3 FAX, IP Fax

**Address Book**  
LDAP (2 000)/Local (1 600)/One-touch (200)

**Send Resolution**  
Push : up to 600 x 600dpi  
Pull : up to 600 x 600dpi

**Communication Protocol**  
File : FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV  
E-mail/i-Fax : SMTP, POP3

**File Format**  
Standard : TIFF, JPEG, PDF (Compact, Searchable, Apply  
policy, Optimize for Web, PDF/A-1b, Trace &  
Smooth, Encrypted, Device Signature, User  
Signature), XPS (Compact, Searchable, Device  
Signature, User Signature), Office Open XML  
(PowerPoint, Word)

## Fax Specifications

**Maximum Number of Connection Lines** 4  
**Modem Speed** Super G3 : 33.6 kbps  
G3 : 14.4 kbps  
**Compression Method** MH, MR, MMR, JBIG

**Resolution:**  
400x400dpi (Ultra Fine), 200x400dpi (Super Fine),  
200x200dpi (Fine), 200x100dpi (Normal)

**Sending/Receiving Size**  
Sending : A3, A4, A4R, A5\*, A5R\*, B4, B5\*, B5R\*<sup>1</sup>  
Receiving : A3, A4, A4R, A5R, B4, B5, B5R  
<sup>1</sup> Sent as A4 <sup>2</sup> Sent as B4 short

**FAX Memory** Up to 30 000 pages (2 000 jobs)  
**Speed Dials** Max. 200

**Group Dials/Destinations** Max. 199 dials  
**Sequential Broadcast** Max. 256 addresses  
**Memory Backup** Yes

## Store Specifications

**Mail Box (Number supported)**  
100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
Maximum 30 000 Pages (2 000 jobs) Stored

**Advanced Box**  
Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows® 8.1/10  
Concurrent Connections (Max.): SMB: 64, WebDAV: 3

**Advanced Box available disc space**  
Standard: 16GB  
(With option: max. 480GB)

## Security Specifications

**Authentication**  
Standard : User Authentication (Picture Login, Picture  
and PIN Login, Card Login, Username and Password  
Login, Function Level Login, Mobile Login), Department ID  
Authentication (Department ID and PIN Login, Function  
Level Login), uniFLOW Online Express (PIN Login, Picture  
Login, Picture and PIN Login, Card Login, Card and PIN  
Login, Username and Password Login, Department ID and  
PIN Login, Function Level Login), Access Management  
System (Access Control)

**Document Security**  
**Print Security** (Secure Print, Encrypted Secure Print, Forced  
Hold Printing, uniFLOW Secure Print\*)

**Receive Data Security** (Confidential Fax Inbox Forwarding  
Received Documents Automatically)

**Scan Security** (Encrypted PDF, Device Signature PDF/  
XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights  
Management ES2.5 Integration), BOX Security (Mail Box  
Password Protected, Advanced Box Access Control)

**Send Data Security** (Setting for requesting password  
input per transmission, Restricted E-mail/File send  
functions, Confirming FAX number, Allow/Restrict Fax Driver  
Transmissions, Allow/Restrict Sending from History, S/MIME  
Support), Document Tracking (Secure Watermark)

\*1 Requires uniFLOW Online/uniFLOW

**Network Security**  
TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0,  
Firewall Functionality (IP/MAC Address Filtering), Dual  
Network Support (Wired LAN/Wireless LAN, Wired LAN/  
Wireless LAN), Disabling Unused Functions (Enabling/  
Disabling Protocols/Applications, Enabling/Disabling  
Remote UI, Enabling/Disabling USB Interface)

**Device Security**  
Protecting HDD Data (HDD Data Encryption (FIPS140-  
2 Validated), HDD Data Overwrite Erase, HDD Lock),  
Standard HDD Initialize, Trusted Platform Module (TPM), Job  
Log Conceal Function, Protecting MFD Software Integrity,  
Checking MFD Software Integrity (Verify System at Startup,  
Runtime Intrusion Detection),  
Optional: IEEE2600.2 (Common Criteria Certification)  
(available at a later schedule)

**Device Management and Auditing**  
Administrator Password, Digital Certificate And Key  
Management, Audit Log, Cooperating with External  
Security Audit System (Security Information and Event  
Management), Image Data Logging, Security Policy Setting

## Environmental Specifications

**Operating Environment**  
Temperature: 10 to 30 °C  
Humidity: 20 to 80 % RH (Relative Humidity)

**Power Source** 220-240V, 50-60Hz, 5.6A

**Power Consumption**  
Maximum: 1 500W  
Standby: Approx. 38 W<sup>1</sup>  
Sleep mode: Approx. 0.9 W<sup>2</sup>

<sup>1</sup> Reference Value (measured one unit)  
<sup>2</sup> 0.9W sleep mode is not available in all circumstances due to certain  
settings.

## Consumables

Toner Cartridge NPG-73 Toner BK  
Toner Yield (Estimated Yield @6% Coverage)  
NPG-73 Toner BK : 42 100 pages

## Software and Printer Management

**Tracking and reporting**  
Universal Login Manager (ULM)  
uniFLOW Online Express

**Remote Management Tools**  
iW Management Console  
eMaintenance  
Content Delivery System

**Scanning Software**  
Network ScanGear

**Optimisation Tools**  
Canon Driver Configuration Tool  
NetSpot Device Installer

**Platform**  
MEAP (Multifunctional Embedded Application Platform)

**Document Publishing**  
iW DESKTOP

## Paper Supply Options

### CASSETTE FEEDING UNIT - AN1

Paper Capacity : 550 Sheets x 2 (80g/m<sup>2</sup>)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A3, A4, A4R, A5R, B4, B5, B5R,  
Custom size : 139.7 x 182.0 mm to 297.0 x 390.0 mm  
Paper Weight : 60 to 220g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions (WxDxH) : 565.0 x 650.0 x 248.0 mm  
(attached to the main unit)  
Weight : Approx. 23.5 kg

### HIGH CAPACITY CASSETTE FEEDING UNIT - B1

Paper Capacity : 2 450 sheets 80g/m<sup>2</sup> (gsm)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A4  
Paper Weight : 60 to 220g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions (WxDxH) : 565.0 x 650.0 x 248.0 mm  
(attached to the main unit)  
Weight : Approx. 28 kg

### PAPER DECK UNIT - F1

Paper Capacity : 2 700 sheets 80g/m<sup>2</sup> (gsm)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A4, B5  
Paper Weight : 60 to 128g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions (W x D x H) : 344.0 x 630.0 x 440.0 mm  
(attached to the main unit)  
Weight : Approx. 31 kg

## Hardware Accessories

**Card Readers**  
COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-B7

**Others**  
PLATEN COVER TYPE-Y2  
ENVELOPE FEEDER ATTACHMENT KIT-D1  
UTILITY TRAY-B1  
NUMERIC KEYPAD-A1

## Security Options

**Device Security**  
iR-ADV SECURITY KIT-AN1 FOR IEEE 2600 COMMON  
CRITERIA CERTIFICATION  
(available at a later schedule)

**Data Security**  
HDD MIRRORING KIT-J1  
6.35cm/250GB HDD-N1  
6.35cm/1TB HDD-P1

## System and Controller Options

**Print Accessories**  
PCL INTERNATIONAL FONT SET-A1  
PCL ASIAN FONT SET-A1  
PS PRINTER KIT-BG1/CC1

**Barcode Printing**  
BARCODE PRINTING KIT-D1

**System Accessories**  
COPY CONTROL INTERFACE KIT-A1  
SERIAL INTERFACE KIT-K3  
CONNECTION KIT-A2 FOR BLUETOOTH LE  
NFC KIT-E1

**Fax Accessories**  
SUPER G3 FAX BOARD-BF1  
SUPER G3 2<sup>nd</sup> LINE FAX BOARD-BF1  
SUPER G3 3<sup>rd</sup>/4<sup>th</sup> LINE FAX BOARD-A1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

## Other Options

**Accessibility Accessories**  
ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1

**Consumables**  
STAPLE-P1  
STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification  
table on your local Canon website.

# MAIN CONFIGURATION OPTIONS



### PLATEN COVER Y2

- Single document scanning

### DADF-BA1

- Multiple document scanning
- 100-sheet duplexing automatic document feeder
- Scans up to 70 images/min (1-sided, 300dpi) and 35 images/min (2-sided, 300)

### SINGLE-PASS DADF-C1

- Single-Pass DADF-C1
- Multiple document scanning 200-sheet duplexing automatic document feeder
- Scans up to 135 images/min (1-sided, 300dpi) and 270 images/min (2-sided, 300dpi)



### BOOKLET FINISHER-Y1

- 2-tray, 3 250 -sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 50 sheets 80g/m<sup>2</sup> (gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



### INNER 2 WAY TRAY-L1

- Separates copies, prints and faxes
- Adds a second internal output tray



### BUFFER PASS UNIT-N1

- Transports paper to external finisher



### INNER FINISHER-J1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports ECO-Stapling 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 40 sheets 80g/m<sup>2</sup> (gsm)
- Supports optional Inner 2/3H Puncher-C1 and 2/F4H Puncher-C1



### STAPLE FINISHER-Y1

- 2-tray, 3 250 -sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports ECO-Staple 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 50 sheets 80g/m<sup>2</sup> (gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



### UTILITY TRAY-B1



### PAPER DECK UNIT-F1

- Supports up to A4
- Media weight 60-128g/m<sup>2</sup> (gsm)
- 2 700 sheets 80g/m<sup>2</sup> (gsm)



### HIGH CAPACITY CASSETTE FEEDING UNIT-B1

- Supports up to A4
- Media weight 60-128g/m<sup>2</sup> (gsm)
- 2 450 sheets 80g/m<sup>2</sup> (gsm)



### CASSETTE FEEDING UNIT-A1

- Supports up to A3
- Media weight 60-128g/m<sup>2</sup> (gsm)
- 2 x 550 sheets 80g/m<sup>2</sup> (gsm)

### METAL PEDESTAL 45/25

- Raises the device, no additional media supply

Images are for reference purpose only. Actual product image may vary.



Partner / Dealer Stamp

To arrange for a demonstration, simply contact:

**CANON INDIA PVT. LTD.**

7<sup>th</sup> Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002  
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

**Disclaimer:** This document is for general information only and contents are subject to change without notice. Errors and omissions accepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte. Ltd.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated

0220W385 © 2020 Canon India Pvt. Ltd.  
All rights reserved. Printed in India.