

**imageRUNNER ADVANCE DX** | **C3730**  
**C3725**  
**C3720**

## Cloud ready document processing with Vivid and Vibrant colour output

The imageRUNNER ADVANCE DX C3700 series provides high productivity with excellent colour output quality. The series provide simple and efficient document processing, making it an excellent partner for daily office tasks.



### WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Industry leading Single-Pass document feeder option allows up to 270 images/min scanning, supports paper skew prevention and comes with advanced anti-dust/streak measures.
- Advance personalisation enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

### COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Seamless integration with output management solutions, such as uniFLOW or uniFLOW Online Express for detailed tracking, reporting and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

## QUALITY AND RELIABILITY

- V<sup>2</sup> (Vivid & Vibrant) imaging technology ensures high quality printouts that impress time after time.
- Supreme transferability of toner and stable reproduction of colours onto a wide range of media, even at large volumes.
- State-of-the-art imaging technologies and toner allow for consistently striking images with 1 200 print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Optional PCL and optional Adobe PostScript®3™ print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

## SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.8W in sleep mode.

## SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- System verification at startup and McAfee® Embedded Control ensures device security, protecting against malware and tampering of firmware.
- Integrate with third-party solutions for complete monitoring protection.

# MACHINE SPECIFICATION

## MAIN UNIT

**Type**  
A3 Colour Laser Multifunctional

**Core Function**  
Print, Copy, Scan, Send, Store and Optional Fax

**Processor**  
Canon Dual Custom Processor (Shared)

**Control Panel**  
25.65 cm (10.1 inch) TFT LCD WSVGA Colour Touch Panel

**Memory**  
Standard: 3.0GB RAM

**Hard Disk Drive**  
Standard\* : 320GB (Available Disk Space: 250GB)  
Optional : 1TB

\*A different initial HDD may be used.

**Interface Connection**  
**Network** Standard : 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

Optional : NFC, Bluetooth Low Energy  
**Others** Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)  
Optional : Serial Interface, Copy Control  
Interface

**Paper Supply Capacity A4, 80g/m<sup>2</sup> (gsm)**  
Standard : 1 200 Sheets (2 x 550-sheet cassettes,  
1 x 100-sheet multi-purpose tray)  
Maximum : 2 300 Sheets (with Cassette Feeding Unit-API)

**Paper Output Capacity A4, 80g/m<sup>2</sup> (gsm)**  
Standard : 250 Sheets  
Maximum : 3 450 Sheets (with Staple Finisher-AA1/  
Booklet Finisher-AA1 and Copy Tray-J2)

**Finishing Capabilities**  
Standard : Collate, Group  
With options : Collate, Group, Offset, Staple, Saddle Stitch,  
Hole Punch, ECO Staple, Staple-On-Demand

**Supported Media Types**  
**Multi-Purpose Tray:**  
Thin, Plain, Heavy\*, Recycled, Coated\*, Color, Tracing, Bond,  
Transparency, Label, Pre-punched, Envelope  
\* SRA3 is unsupported for Coated 257-300g/m<sup>2</sup> (gsm) and Heavy 257-300g/m<sup>2</sup> (gsm)  
paper.

**Paper Cassette 1:**  
Thin, Plain, Heavy, Recycled, Color, Bond, Transparency,  
Pre-punched, Envelope

**Paper Cassette 2:**  
Thin, Plain, Heavy, Recycled, Color, Bond, Transparency,  
Pre-punched, Envelope\*

\* Envelope Feeder Attachment A (standard) is required.

**Supported Media Sizes**  
**Multi-Purpose Tray:**  
Standard size : SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5,  
B5R, Foolscap, India legal, F4A

Custom size : 98.4 x 139.7 mm to 320.0 x 457.2 mm  
Free size : 98.4 x 139.7 mm to 320.0 x 457.2 mm  
Envelopes : COM10 No.10, Monarch, ISO-C5, DL  
Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm

**Paper Cassette 1:**  
Standard size : A4, A5, A5R, A6R, B5  
Custom Size : 105.0 x 148.0 mm to 297.0 x 215.9 mm  
Envelopes : ISO-C5

**Paper Cassette 2:**  
Standard size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,  
Foolscap, India legal, F4A  
Custom Size : 105.0 x 148.0 mm to 304.8 x 457.2 mm  
Envelopes\* : COM10 No.10, Monarch, DL

\* Envelope Feeder Attachment A (standard) is required.

**Supported Media Weights**  
Multi-Purpose Tray\* : 52 to 300g/m<sup>2</sup> (gsm)  
Paper 1/2 Cassettes : 52 to 220g/m<sup>2</sup> (gsm)  
Duplex : 52 to 220g/m<sup>2</sup> (gsm)  
\* SRA3 is unsupported for Coated 257-300g/m<sup>2</sup> (gsm) and Heavy 257-300g/m<sup>2</sup> (gsm)  
paper.

**Warm-up Time**  
Quick Startup Mode : 4s or less\*  
From Sleep Mode : 10s or Less  
From Power On : 10s or Less\*

\*Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

\*Time from device power-on, until copy ready (not print reservation)

**Dimensions (W x D x H)**  
With Platen Cover-Y2 : 565.0 x 692.0 x 777.0 mm  
With Single Pass DADF-C1 : 565.0 x 722.0 x 887.0 mm  
With DADF-BA1 : 565.0 x 719.0 x 880.0 mm

**Installation Space (W x D)**  
Basic: 978.0 x 1118.0 mm (with Single Pass DADF-C1 + right  
cover open + Multi-purpose tray extension extended  
+ paper cassette open)  
978.0 x 1115.0 mm (with DADF-BA1 + right cover open +  
Multi-purpose tray extension extended + Paper  
cassette open)

Fully Configured:  
1 651.0 x 1118.0 mm (with Single Pass DADF-C1 +  
Staple Finisher-AA1/Booklet Finisher-AA1 +  
Copy Tray-J2 extension extended + paper cassette  
open)  
1 651.0 x 1115.0 mm (with DADF-BA1 + Staple Finisher-  
AA1/Booklet Finisher-AA1 + Copy Tray-J2 extension  
extended + paper cassette open)

**Weight**  
With Platen Cover-Y2 : Approx. 66.7 kg including toner  
With DADF-BA1 : Approx. 73.1 kg including toner  
With Single Pass DADF-C1 : Approx. 79.6 kg including toner

## Printing Specifications

**Print Speed (BW and CL)**  
iR-ADV DX C3730: up to 30 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)  
iR-ADV DX C3725: up to 25 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)  
iR-ADV DX C3720: up to 20 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)

**Print Resolution**  
600 x 600dpi, 1200 x 1200dpi (half speed)

**Page Description Languages**  
Standard : UFR II  
Option : Adobe® PostScript®3™, PCL6

**Direct Print**  
Supported file types: PDF, EPS, TIFF/JPEG, and XPS

**Printing from Mobile and Cloud**  
AirPrint, Mopria, Google Cloud Print, Canon Print Business,  
and uniFLOW Online

**Fonts**  
PS fonts : 136 Roman  
PCL fonts : 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T<sup>1</sup> (Japanese, Korean, Simplified  
and Traditional Chinese), Barcode fonts<sup>2</sup>

\*1 Requires optional PCL International Font Set-A1

\*2 Requires optional Barcode Printing Kit-D1

**Operating System**  
UFRII: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019  
PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)

## Copy Specifications

**Copy Speed (Bw and CL)**  
iR-ADV DX C3730: up to 30 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)  
iR-ADV DX C3725: up to 25 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)  
iR-ADV DX C3720: up to 20 pages/min (A4/A5/A5R/A6R)  
up to 15 pages/min (A3)  
up to 20 pages/min (A4R)

**First-Copy-Out Time (A4, BW/CL)**  
Approx. 5.9/8.2 s or less

**Copy Resolution** : 600 x 600dpi  
**Multiple Copies** : Up to 999 copies  
**Copy Exposure** : Automatic or Manual (9 Levels)  
**Magnification** : Variable zoom  
: 25% to 400% (1% Increments)  
Preset reduction/enlargement:  
25%, 50%, 61%, 70%, 81%, 86%,  
100% (1:1), 115%, 122%, 141%,  
200%, 400%

## Scan Specifications

### Type

Standard: Colour Flatbed Scan Unit  
Optional: Platen Cover, Single Pass DADF-C1\* or DADF-BA1  
[2-sided to 2-sided (Automatic with DADF)]

\* Detect Feeder Multi Sheet Feed is supported.

### Document Feeder Paper Capacity 80g/m<sup>2</sup> (gsm)

Single Pass DADF-C1 : up to 200 Sheets  
DADF-BA1 : up to 100 Sheets

### Acceptable originals and weights

Platen: Sheet, Book, and 3-Dimensional Objects  
Document Feeder media weight:

Single Pass DADF-C1:

1-sided scanning: 38 to 220g/m<sup>2</sup> (gsm) (BW, CL)

2-sided scanning: 38 to 220g/m<sup>2</sup> (gsm) (BW, CL)

\*An acceptable weights of A6R or smaller is 50 to 220g/m<sup>2</sup> (gsm).

DADF-BA1:

1-sided scanning: 38 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)

2-sided scanning: 50 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)

### Supported Media Sizes

Platen max. scanning size: up to 297.0 x 431.8 mm  
Single Pass DADF-C1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R

Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

DADF-BA1: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6

Custom size: 139.7 x 128.0 mm to 297.0 x 431.8 mm

### Scan Speed (BW/CL, A4)

#### Single Pass DADF-C1:

1-sided Scanning: 135/135 images/min (300 x 300, send), 51/51 images/min (600 x 600, copy)

2-sided Scanning: 270/270 images/min (300 x 300, send), 51/51 images/min (600 x 600, copy)

#### DADF-BA1:

1-sided Scanning: 70/70 images/min (300 x 300, send), 51/51 images/min (600 x 600, copy)

2-sided Scanning: 35/35 images/min (300 x 300, send), 25.5/25.5 images/min (600 x 600, copy)

### Scan Resolution

Scan for Copy: 600 x 600dpi

Scan for Send: (Push) 600 x 600dpi (SMB/FTP/WebDAV/

IFAX), (Pull) 600 x 600dpi

Scan for Fax: 600 x 600dpi

### Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

## Send Specifications

### Destination

Standard : E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box

Optional : Super G3 FAX, IP Fax

### Address Book

LDAP (2 000)/Local (1 600)/One-touch (200)

### Send Resolution

Push : up to 600 x 600dpi

Pull : up to 600 x 600dpi

### Communication Protocol

File : FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV

E-mail/I-Fax : SMTP, POP3

### File Format

Standard : TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

## Fax Specifications

### Maximum Number of Connection Lines 2

Modem Speed Super G3 : 33.6 kbps  
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution 400x400dpi (Ultra Fine),  
200x400dpi (Super Fine),  
200x200dpi (Fine),  
200x100dpi (Normal)

### Sending/Receiving Size

Sending : A3, A4, A4R, A5<sup>1</sup>, A5R<sup>1</sup>, B4, B5<sup>2</sup>, B5R<sup>1</sup>

Receiving : A3, B4, A4, A4R, A5R, B5, B5R

\*1 Sent as A4 \*2 Sent as B4 short

FAX Memory Up to 30 000 pages (2 000 jobs)

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

## Store Specifications

### Mail Box Simple (Number supported)

100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
Maximum 10 000 Pages (2 000 jobs) Stored

### Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows® 8.1/10

Concurrent Connections (Max.): SMB: 64, WebDAV: 3

### Advanced Box available disc space

Approx. 16GB (Standard HDD)

Approx. 480GB (with option 1TB HDD)

## Security Specifications

### Authentication and Access Control

Standard : User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

### Document Security

**Print Security** (Secure Print, Encrypted Secure Print,

Forced Hold Printing, uniFLOW Secure Print<sup>1</sup>)

**Receive Data Security** (Confidential Fax Inbox Forwarding Received Documents Automatically)

**Scan Security** (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control)

**Send Data Security** (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

\*1 Requires uniFLOW Online/uniFLOW

### Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface)

### Device Security

Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Optional: IEEE2600.2 (Common Criteria Certification) (available at a later schedule)

### Device Management and Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

## Environment Specifications

### Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

220-240V, 50/60Hz, 4A

### Power Consumption

Maximum: 1 500 W

Standby: Approx. 45.1 W<sup>\*1</sup>

Sleep mode: Approx. 0.8 W<sup>\*2</sup>

\*1 Reference Value

\*2 0.8W sleep mode is not available in all circumstances due to certain settings.

## Consumables

Toner Cartridge NPG-67 Toner BK/C/M/Y

Toner Yield (Estimated Yield @5% Coverage)

NPG-67 Toner BK : 36 000 pages

NPG-67 Toner C/M/Y : 19 000 pages

NPG-67L Toner C/M/Y : 2 500 pages

## Software and Printer Management

### Tracking and reporting

Universal Login Manager (ULM)

uniFLOW Online Express

### Remote Management Tools

iW Management Console

eMaintenance

Content Delivery System

### Scanning Software

Network ScanGear

### Optimisation Tools

Canon Driver Configuration Tool

NetSpot Device Installer

### Platform

MEAP (Multifunctional Embedded Application Platform)

### Document Publishing

IW DESKTOP

## Paper Supply Options

### CASSETTE FEEDING UNIT-API

Paper Capacity : 550 sheets x 2 (1 100 sheets, 80g/m<sup>2</sup> (gsm))

Paper Type : Thin, Plain, Recycled, Color, Heavy Bond, Transparency, Pre-punched

Paper Size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Foolsap, India Legal, F4A

Custom size : 105.0 x 148.0 mm to

304.8 x 457.2 mm

Paper Weight : 52 to 220g/m<sup>2</sup> (gsm)

Power Source : From the Main Unit

Dimensions : (WxDxH) 565.0 x 615.0 x 248.0 mm

Weight : Approx. 16.0 kg

## Hardware Accessories

### Card Readers

COPY CARD READER-F1

COPY CARD READER ATTACHMENT-B7

### Others

UTILITY TRAY-B1

NUMERIC KEYPAD-A1

PLATEN COVER-Y2

3 WAY UNIT-D1

## Security Options

### Device Security

IR-ADV SECURITY KIT-AM1 FOR IEEE 2600 COMMON

CRITERIA CERTIFICATION

(available at a later schedule)

### Data Security

6.35cm/1TB HDD-P1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1

PCL ASIAN FONT SET-A1

PS PRINTER KIT-BJ1/CD1

### Barcode Printing

BARCODE PRINTING KIT-D1

### System Accessories

SERIAL INTERFACE KIT-K3

COPY CONTROL INTERFACE KIT-A1

CONNECTION KIT-A2 FOR BLUETOOTH LE

NFC KIT-E1

### Fax Accessories

SUPER G3 FAX BOARD-AZ1

SUPER G3 2<sup>ND</sup> LINE FAX BOARD-AU1

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1

VOICE GUIDANCE KIT-G1

VOICE OPERATION KIT-D1

### Staple Cartridge

STAPLE-P1

STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification table on your local Canon website.

# MAIN CONFIGURATION OPTIONS



### BOOKLET FINISHER-AA1

- 2-tray, 3 250 -sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports optional external 2/3 and 2/F4 hole punchers (2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1)



### STAPLE FINISHER-AA1

- 2-tray, 3 250 -sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports ECO-Staple 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports optional external 2/3 and 2/F4 hole punchers (2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1)



### INNER 2 WAY TRAY-J1

- Separates copies, prints and faxes
- Adds a second internal output tray



### INNER FINISHER - K1

- 2-tray, 600 -sheet capacity
- Corner and double stapling up to 50 sheets 80g/m<sup>2</sup> (gsm)
- Supports ECO-Staple 4 sheets 80g/m<sup>2</sup> (gsm) and Staple-On-Demand 40 sheets 80g/m<sup>2</sup> (gsm)



### PLATEN COVER Y2

- Single document scanning



### DADF - BA1

- Multiple document scanning
- 100-sheet duplexing automatic document feeder
- Scans up to 70 images/min (1-sided, 300) and 35 images/min (2-sided, 300)



### SINGLE-PASS DADF-C1

- Multiple document scanning
- 200-sheet duplexing automatic document feeder
- Scans up to 135 images/min (1-sided, 300) and 270 images/min (2-sided, 300)



### UTILITY TRAY B1



### COPY TRAY-J2



### METAL PEDESTAL 35/30

Raises the device, no additional media supply

### CASSETTE FEEDING UNIT-API

- Supports up to A3
- Media weight 52 – 220g/m<sup>2</sup> (gsm)
- 2 x 550 sheets 80g/m<sup>2</sup> (gsm)

Images are for reference purpose only. Actual product image may vary.



V<sup>2</sup> COLOUR



Partner / Dealer Stamp

To arrange for a demonstration, simply contact:

**CANON INDIA PVT. LTD.**

7<sup>th</sup> Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002  
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

**Disclaimer:** This document is for general information only and contents are subject to change without notice. Errors and omissions accepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte. Ltd.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated

0220W283 © 2020 Canon India Pvt. Ltd.  
All rights reserved. Printed in India.